



HANGLORY



# Empowering Garment Competitiveness



## Wings Pro

### DTG-Direct to Garment Digital Printer

- Online pre-treatment for smart and efficient operations, enabling a "one person, one machine" workflow.
- Equipped with 32 grayscale industrial print heads, achieving a high printing accuracy of 600x1800 DPI.
- High production efficiency for both dark and light-colored fabrics.
- Real-time tracking of digital printing for a convenient and smart operation.
- Environmentally friendly with a pollution-free process.
- Original ink circulation system, far away from printhead clogging.
- Fully self-developed design, supporting machine upgrades and custom pallet options.



Intelligent



Fast




Productive



Personalized

## Specifications

|               |                     |  |
|---------------|---------------------|--|
| Print         | Productivity        | In-line pretreat:240pcs/h<br>Off-line pretreat:400pcs/h      |
|               | Printing Height     | 2-3mm (0.08"x0.12")  |
|               | Max. Image Area     | 400x500 mm (15.75"x19.69")                                   |
|               | Fabric Types        | Pure cotton or mixed cotton fabric                           |
| Print heads   | Printheads Quantity | 16-32  |
|               | Printheads          | Grayscale Industrial Printhead                               |
|               | Printing Resolution | 600x1200/1800dpi   |
|               | Cleaning System     | Automatic cleaning system                                    |
|               | Moisturizing        | Non-contact Moisturizing                                     |
| Pallet        | Pallet Quantity     | 16   |
| Machine       | Overall Size        | 6500x4500x2000mm (LxWxH)                                     |
|               | G.W.                | 4620kg   |
| Ink           | Ink Type            | Pigment ink  |
|               | Ink Channel         | CMYK+White   |
| Soft ware     | RIP Software        | Wings Pro dedicated RIP software                             |
|               | Operating           | Windows  |
| Requi rements | Temperature         | 20°C-25°C  |
|               | Relative Humidity   | 60%-70%  |
|               | Power Supply        | Equipment : AC 380V 30A(20KW)<br>Drying : AC 380V 120A(80KW) |
|               | Compressed Air      | 0.6 Mpa  |



**One piece every 10-15 seconds**

© The above information is only for your reference. SHENZHEN CNTOP DIGITAL EQUIPMENT CO.,LTD reserves the right of final interpretation. If changes are made without prior notice, the final information will be subject to the contract.



**Shenzhen CNTOP Digital Equipment Co.,Ltd**

Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen China.  
(2-3/F, BuildingC, Jingmida Digital Culture Industry Park- HanGloryGroup)  
Fax:+860755-23217841  
Web:www.hanglorygroup.com/en



**HANGLORY**

