



*Illustration purpose

Technical Parameters:

Model		HT1800UV
Printing Information		
Printhead		GEN6
Number of Printheads		2 - 8 pcs (3-row)
Resolution		605*1800 DPI
Productivity	Draft Mode	65 m²/h
	Production Mode	56 m²/h
	Quality Mode	41 m²/h
Printing Modes		Unidirectional & Bidirectional
Media & Ink		
Max. Print Width		1800 mm
Max. Media Thickness		50 mm
Media		Flexible flat materials
Ink Type		UV (VOC free)
Ink Colors		CMYK, Lc, Lm, W
Features		
Curing		Water-cooled UV_LED Lamp
Transfer		USB
RIP Support		Caldera / Onyx (Optional Purchase)
Input		PDF, JPEG, TIFF, EPS, AI.....
Dimensions & Weight		
Printer Dimensions		4515*960*1335 mm (L*W*H)
Net Weight		1200 KG
Gross Weight		1500 KG
Power & Environment		
Power Consumption		4 kW (19A)
Power Supply		220VAC 50Hz 3P/N/PE
Environmental Requirements		Independent, clean, low-dust, low-light workspace with good ventilation
		Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)
		Relative Humidity: 30% ~ 70% (non-condensing)
Others		Requires ADP / Computer

Industrial Digital Inkjet Comprehensive Solution Provider



Independent
printhead-drive
technology



Self-developed
control system



Self-developed
MES system



Independent ink
industrial chain



Remote service
maintenance system
and local services